



SoundWall™ H SERIES SPECIFICATIONS

SPECIFICATIONS	IN-8H	IN-6H	IN-5H
Construction	Front baffle black printed MDF	Front baffle black printed MDF	Front baffle black printed MDF
Drive units	<p>Woofers: 8" DPC cone 3" Hexatech™ voice coil, External Voice Coil technology (EVC)</p> <p>Tweeter: 1.1" soft dome, Acuflex™ coated, Hexatech™ voice coil, double neodymium magnet motor</p>	<p>Woofers: 6" DPC cone 3" Hexatech™ voice coil, External Voice Coil technology (EVC)</p> <p>Tweeter: 1.1" soft dome, Acuflex™ coated, Hexatech™ voice coil, double neodymium magnet motor</p>	<p>Woofers: 5" DPC cone 3" Hexatech™ voice coil, External Voice Coil technology (EVC)</p> <p>Tweeter: 1.1" soft dome, Acuflex™ coated, Hexatech™ voice coil, double neodymium magnet motor</p>
Nominal impedance	6 ohm	6 ohm	6 ohm
Sensitivity 2.83V/1M	90 dB	88 dB	86 dB
Power handling	180W	120W	100W
Operating power	20-200 W	20-150 W	20-120 W
Crossover	2,200Hz / 12 dB	2,200Hz / 12 dB	2,200Hz / 12 dB
Frequency response	30-22,000 Hz	38-22,000 Hz	45-22,000 Hz
Tweeter level adjustment	0 / ±2 dB	0 / ±2 dB	0 / ±2 dB
Grille	Metal	Metal	Metal
Overall Exterior Frame Dimensions (WxHxD)	10.4" x 14.1" x 3.3" (263 x 357 x 83 mm)	8.7" x 12" x 3.2" (220 x 305 x 82 mm)	.5" x 10.7" x 3.3" (191x 272 x 83 mm)
Finish	White	White	White

* Morel operates a policy of continuous products design improvement, consequently specifications are subject to alteration without prior notice.